

STATE OF CONNECTICUT

CONNECTICUT SITING COUNCIL

Ten Franklin Square, New Britain, CT 06051

Phone: (860) 827-2935 Fax: (860) 827-2950

E-Mail: siting.council@po.state.ct.us

www.ct.gov/csc

April 21, 2005

Kenneth C. Baldwin, Esq.
Robinson & Cole LLP
280 Trumbull Street
Hartford, CT 06103-3597

RE: **EM-VER-026-060-070-070A-050317** -Cellco Partnership d/b/a Verizon Wireless notice of intent to modify existing telecommunications facilities located at 1919 Boston Post Road, Guilford; 49 Wig Hill Road, Chester; Route 80, Killingworth; and Chestnut Hill Road, Killingworth, Connecticut.

Dear Attorney Baldwin:


At a public meeting held on April 19, 2005, the Connecticut Siting Council (Council) acknowledged your notice to modify these existing telecommunications facilities, pursuant to Section 16-50j-73 of the Regulations of Connecticut State Agencies.

The proposed modifications are to be implemented as specified here and in your notice dated March 17, 2005, including the placement of all necessary equipment and shelters within the tower compounds. The modifications are in compliance with the exception criteria in Section 16-50j-72 (b) of the Regulations of Connecticut State Agencies as changes to existing facility sites that would not increase tower heights, extend the boundaries of the tower sites, increase noise levels at the tower site boundaries by six decibels, and increase the total radio frequencies electromagnetic radiation power densities measured at the tower site boundaries to or above the standard adopted by the State Department of Environmental Protection pursuant to General Statutes § 22a-162. These facilities have also been carefully modeled to ensure that radio frequency emissions are conservatively below State and federal standards applicable to the frequencies now used on these towers.

This decision is under the exclusive jurisdiction of the Council. Any additional change to any of these facilities will require explicit notice to this agency pursuant to Regulations of Connecticut State Agencies Section 16-50j-73. Such notice shall include all relevant information regarding the proposed change with cumulative worst-case modeling of radio frequency exposure at the closest point of uncontrolled access to the tower base, consistent with Federal Communications Commission, Office of Engineering and Technology, Bulletin 65. Any deviation from this format may result in the Council implementing enforcement proceedings pursuant to General Statutes § 16-50u including, without limitation, imposition of expenses resulting from such failure and of civil penalties in an amount not less than one thousand dollars per day for each day of construction or operation in material violation.

Thank you for your attention and cooperation.

Very truly yours,


Pamela B. Katz, P.E.
Chairman

PBK/laf

c: See Attached List

Recipient List:


The Honorable Martin L. Heft, First Selectman, Town of Chester
Cathy Jefferson, Zoning Enforcement Officer, Town of Chester
The Honorable David L. Denvir, First Selectman, Town of Killingworth
Cathie Jefferson, Zoning Enforcement Officer, Town of Killingworth
The Honorable Charles E. Bishop, First Selectman, Town of Guilford
Regina Reid, Zoning Enforcement Officer, Town of Guilford
Thomas J. Regan, Brown Rudnick Berlack Israels, LLP
Stephen J. Humes, Esq., McCarter & English LLP
Christopher B. Fisher, Esq., Cuddy & Feder, LLP
Thomas F. Flynn III, Nextel Communications
Jeffrey W. Barbadora, Crown Atlantic Company LLC

EM-VER-026-060-070-070A-050317

280 Trumbull Street
Hartford, CT 06103-3597
Main (860) 275-8200
Fax (860) 275-8299
kbaldwin@rc.com
Direct (860) 275-8345

March 17, 2005

Via Hand Delivery



S. Derek Phelps
Executive Director
Connecticut Siting Council
10 Franklin Square
New Britain, CT 06051

Re: **Notice of Exempt Modification – Antenna Swap**
Guilford 2—1919 Boston Post Road, Guilford, CT
Chester—49 Wig Hill Road, Chester, CT
Killingworth—Route 80, Killingworth, CT
Killingworth 2—Chestnut Hill Road, Killingworth, CT

Dear Mr. Phelps:

Cellco Partnership d/b/a Verizon Wireless (“Cellco”) currently maintains a wireless telecommunications facility at each of the sites referenced above. As discussed below, Cellco now intends to modify each of these facilities.

Please accept this letter as notification pursuant to R.C.S.A. § 16-50j-73, for construction that constitutes an exempt modification pursuant to R.C.S.A. § 16-50j-72(b)(2). In accordance with R.C.S.A. § 16-50j-73, a copy of this letter is being sent to the chief elected or appointed official in each affected municipality.



Guilford 2 Facility – 1919 Boston Post Road

Cellco’s existing facility consists of twelve (12) cellular antennas on a tower owned by the SprintSites, USA. Cellco now intends to modify its facility by replacing six (6) of its cellular antennas with six (6) PCS antennas at the same level on the tower. Attached behind Tab 1 are specifications for the existing cellular antennas and the proposed PCS antennas for the Guilford 2 facility and a new general power density table.

Law Offices

BOSTON

HARTFORD

NEW LONDON

STAMFORD

GREENWICH

WHITE PLAINS

NEW YORK CITY

SARASOTA

www.rc.com

HART1-1241626-1

S. Derek Phelps
March 17, 2005
Page 2

Chester Facility – 49 Wig Hill Road

Cellco's existing facility consists of twelve (12) cellular antennas on a tower owned by Crown Atlantic Company, LLC. Cellco now intends to modify its facility by replacing six (6) of its cellular antennas with six (6) PCS antennas at the same level on the tower. Attached behind Tab 2 are specifications for the existing cellular antennas and the proposed PCS antennas for the Chester facility and a new general power density table.

Killingworth Facility – Route 80

Cellco's existing facility consists of twelve (12) cellular antennas on a tower owned by Crown Atlantic Company, LLC. Cellco now intends to modify its facility by replacing six (6) of its cellular antennas with six (6) PCS antennas at the same level on the tower. Attached behind Tab 3 are specifications for the existing cellular antennas and the proposed PCS antennas for the Killingworth facility and a new general power density table.

Killingworth 2 Facility – Chestnut Hill Road

Cellco's existing facility consists of twelve (12) cellular antennas on a tower owned by Crown Atlantic Company, LLC. Cellco now intends to modify its facility by removing six (6) of its cellular antennas and replacing them with nine (9) PCS antennas, for a total of fifteen (15) antennas, at the same level on the tower. Attached behind Tab 4 are specifications for the existing cellular antennas and the proposed PCS antennas for the Killingworth 2 facility, a new general power density table and a structural analysis stating that the tower can support the proposed modification.

The planned modifications to each facility falls squarely within those activities explicitly provided for in R.C.S.A. § 16-50j-72(b)(2).

1. The proposed modifications will not result in any increase in the overall height of any of the existing structures. Cellco's replacement antennas will be mounted at the same level on the tower.
2. The proposed modifications will not affect ground-mounted equipment and will not require the extension of the site boundaries.
3. The proposed modifications will not increase noise levels at the facility by six decibels or more.



ROBINSON & COLE^{LLP}

S. Derek Phelps
March 17, 2005
Page 3

4. The proposed modifications will not result in radio frequency (RF) power density levels at the facility that exceed the Federal Communications Commission (FCC) adopted safety standard.

For the foregoing reasons, Cellco respectfully submits that the proposed modifications to the above-referenced telecommunications facilities constitute an exempt modification under R.C.S.A. § 16-50j-72(b)(2).

Sincerely,



Kenneth C. Baldwin

Enclosures

cc: Charles E. Bishop, Town of Guilford First Selectman
Martin L. Heft, Town of Chester First Selectman
David L. Denvir, Town of Killingworth First Selectman
Sandy M. Carter



ALP 8013-N


Log-Periodic Reflector Antenna

80 Degrees 13 dBd

Features:


- ☐ Broadbanded. (800-900 MHz)
- ☐ Low backlobe radiation. Front-to-back ratio better than 30 dB
- ☐ Low Intermodulation Products.
- ☐ Low Wind-load.
- ☐ Low weight.
- ☐ Small size.
- ☐ Rugged design.

Please see the following pages including radiation patterns/tables for ALP 8013-N.



Electrical Specifications:

Frequency range:	806-896 MHz
Impedance:	50 ohm
Connector:	N-female or 7/8" EIA
VSWR:	Typ. 1.3:1 max 1.5:1
Polarization:	Vertical
Gain:	13 dBd
Front to back ratio:	>30 dB
Side-lobe suppression:	>18 dB
Intermodulation: (2x25W):	IM3 >146 dB IM5 >153 dB IM7 & IM9 >163 dB
Power Rating:	500 W
H-Plane: -3 dB	84 °
E-Plane: -3 dB	15 °
Lightning Protection:	DC Grounded



Mechanical Specifications:

Overall Height:	52 in	(1320 mm)
Width:	13 in	(330 mm)
Depth:	11.4 in	(290 mm)
Weight including brackets:	27.3 lbs	(12.3 Kg)
Rated wind velocity:	113 mph	(180 Km/h)
Wind Area (Cx A/Front):	4.5 sq.ft	(0.42 sq.m)
Lateral thrust at rated wind		
Worst case:	650 N	

Materials:

Radiating elements:	Aluminum
Element housing:	Grey PVC
Back-plate:	Aluminum
Mounting hardware	
clamps:	Hot dip galvanized steel
bolts:	Stainless steel

Manufactured by: Allgon System AB

DECIBEL
Base Station Antennas

948F85T2E-M

16.1 dBi, Directed Dipole Antenna
1850-1990 MHz


1850-1990 MHz

MaxFill™


dB Director®

- Exceptional azimuth roll-off reducing soft hand-offs and improving capacity
- Excellent upper side lobe suppression
- Deep null filling below the horizon assures improved signal intensity
- Low profile appearance and low wind loading profile for easier zoning approvals


850



Azimuth 1850 MHz (Tilt=2)



Vertical 1850 MHz (Tilt=2)



Horizontal 1850 MHz (Tilt=2)



ELECTRICAL

Frequency (MHz):	1850-1990
Polarization:	Vertical
Gain (dBd/dBi):	14/16.1
Azimuth BW:	85°
Elevation BW:	8°
Beam Tilt:	2°
USLS* (dB):	>18
Null Fill* (dB):	15
Front-to-Back Ratio* (dB):	40
VSWR:	<1.33:1
IM Suppression - Two 20 Watt Carriers:	-150 dBc
Impedance:	50 Ohms
Max Input Power:	250 Watts
Lightning Protection:	DC Ground
Opt Electrical Tilt:	0°, 4°, 6°

MECHANICAL

Weight:	8.5 lbs (3.9 kg)
Dimensions (LxWxD):	48 X 3.5 X 7 in (1219 X 89 X 178 mm)
Max. Wind Area:	1.18 ft² (0.11 m²)
Max. Wind Load (@ 100mph):	65 lbf (289 N)
Max. Wind Speed:	125 mph (201 km/h)
Radiator Material:	Low Loss Circuit Board
Reflector Material:	Aluminum
Radome Material:	ABS, UV Resistant
Mounting Hardware Material:	Galvanized Steel
Connector Type:	7-16 DIN - Female (Bottom)
Color:	Light Gray
Standard Mounting Hardware:	DB390 Pipe Mount Kit, included
Downtilt Mounting Hardware:	DB5098, optional
Opt. Mounting Hardware:	DB5094-AZ Azimuth Wall Mount



Andrew Corporation
8635 Stemmons Freeway
Dallas, Texas U.S.A 75247-3701
Tel: 214.631.0310

Fax: 214.631.4706
Toll Free Tel: 1.800.676.5342
Fax: 1.800.229.4706
www.andrew.com

Date: 4/29/2004
* - Indicates Typical Values

dbtech@andrew.com

General Power Density

Site Name: Guilford 2, CT
Tower Height: 122 FT

Operator	Operating Frequency (MHz)	Number of Trans.	ERP Per Trans. (watts)	Total ERP (watts)	Distance to Target (feet)	Calculated Power Density (mW/cm ²)	Maximum Permissible Exposure (mW/cm ²)	Fraction of MPE (%)
Verizon	880	9	200	1800	122	0.0435	0.586	7.42%
Verizon	1900	3	200	600	122	0.0145	1	1.45%
Total Percentage of Maximum Permissible Exposure								8.87%

*Guidelines adopted by the FCC on August 1, 1996, 47 CFR Part 1 based on NCRP Report 86, 1986 and generally on ANSI/IEEE C95.1-1992

MHz = Megahertz
mW/cm² = milliwatts per square centimeter
ERP = Effective Radiated Power





844H90EXYBAM


12 dBd
Log Periodic Antenna

824-896 MHz

dB Director®


- Superior Azimuth pattern roll off, reducing sector to sector interference, improving call capacity.
- Extremely rugged, reliable design yet lightweight with low wind load.

90°



Azimuth
(Horizontal)


Elevation
(Vertical)



Scale: 10° radials, 5 dB per division

Electrical

Frequency:	824-896 MHz
Polarization:	Vertical
Gain:	12 dBd (14.1 dBi)
Azimuth BW:	90°
Elevation BW:	15.5°
USLS:	> 18 dB
Front-to-Back Ratio:	40 dB
VSWR:	1.22:1
PIM:	-150 dBc (2 tone, 20 watt)
Impedance:	50 Ohms
Max. Input Power:	500 Watts
Lightning Protection:	All metal parts are grounded



Mechanical

Weight:	10 lbs (4.5 kg)
Dimensions:	48" x 6" x 8.5" (1219 x 152 x 216 mm)
Max. Wind Area:	2.8 ft² (0.26 m²)
Max. Wind Load:	80 lbf (356N) 35.9 kp (at 100 mph)
Max. Wind Speed:	125 mph (201 km/h)
Radiators:	Brass
Reflector:	Pass. Aluminum
Radome:	ABS, UV Resistant
Mounting Hardware:	Galvanized Steel
Connector:	7/16 DIN (Back)
Color:	Gray

Mounting Options

Standard:	DB380 pipe mount kit included.
Downtilt:	DB5083 downtilt brackets, optional.

8635 Stemmons Freeway • Dallas, Texas U.S.A. 75247-3701
Dallas/Ft.Worth Area Tel: 214.631.0310 • Fax: 214.631.4706
Toll Free Tel: 1.800.676.5342 • Fax: 1.800.229.4706

www.decibelproducts.com
dbtech@decibelproducts.com

099089-052 05/02-B



ISO9001 Compliant

DECIBEL
Base Station Antennas

948F85T2E-M

16.1 dBi, Directed Dipole Antenna
1850-1990 MHz


1850-1990 MHz

MaxFill™


dB Director®

- Exceptional azimuth roll-off reducing soft hand-offs and improving capacity
- Excellent upper side lobe suppression
- Deep null filling below the horizon assures improved signal intensity
- Low profile appearance and low wind loading profile for easier zoning approvals


85°



Azimuth 1850 MHz (Tilt=2)



Vertical 1850 MHz (Tilt=2)



Horizontal 1850 MHz (Tilt=2)



ELECTRICAL

Frequency (MHz):	1850-1990
Polarization:	Vertical
Gain (dBd/dBi):	14/16.1
Azimuth BW:	85°
Elevation BW:	8°
Beam Tilt:	2°
USLS* (dB):	>18
Null Fill* (dB):	15
Front-to-Back Ratio* (dB):	40
VSWR:	<1.33:1
IM Suppression - Two 20 Watt Carriers:	-150 dBc
Impedance:	50 Ohms
Max Input Power:	250 Watts
Lightning Protection:	DC Ground
Opt Electrical Tilt:	0°, 4°, 6°

MECHANICAL

Weight:	8.5 lbs (3.9 kg)
Dimensions (LxWxD):	48 X 3.5 X 7 in (1219 X 89 X 178 mm)
Max. Wind Area:	1.18 ft² (0.11 m²)
Max. Wind Load (@ 100mph):	65 lbf (289 N)
Max. Wind Speed:	125 mph (201 km/h)
Radiator Material:	Low Loss Circuit Board
Reflector Material:	Aluminum
Radome Material:	ABS, UV Resistant
Mounting Hardware Material:	Galvanized Steel
Connector Type:	7-16 DIN - Female (Bottom)
Color:	Light Gray
Standard Mounting Hardware:	DB390 Pipe Mount Kit, included
Downtilt Mounting Hardware:	DB5098, optional
Opt. Mounting Hardware:	DB5094-AZ Azimuth Wall Mount



Andrew Corporation
8635 Stemmons Freeway
Dallas, Texas U.S.A 75247-3701
Tel: 214.631.0310

Fax: 214.631.4706
Toll Free Tel: 1.800.676.5342
Fax: 1.800.229.4706
www.andrew.com

Date: 4/29/2004
* - Indicates Typical Values

dbtech@andrew.com

General Power Density

Site Name: Chester, CT
Tower Height: 140 FT

Operator	Operating Frequency (MHz)	Number of Trans.	ERP Per Trans. (watts)	Total ERP (watts)	Distance to Target (feet)	Calculated Power Density (mW/cm ²)	Maximum Permissible Exposure* (mW/cm ²)	Fraction of MPE (%)
Verizon	880	9	200	1800	140	0.0330	0.586	5.64%
Verizon	1900	3	200	600	140	0.0110	1	1.10%
Total Percentage of Maximum Permissible Exposure								6.74%

*Guidelines adopted by the FCC on August 1, 1996, 47 CFR Part 1 based on NCRP Report 86, 1986 and generally on ANSI/IEEE C95.1-1992

MHz = Megahertz

mW/cm² = milliwatts per square centimeter

ERP = Effective Radiated Power



General Power Density

Site Name: Killingworth, CT
Tower Height: 160 FT

Operator	Operating Frequency	Number of Trans.	ERP Per Trans.	Total ERP	Distance to Target	Calculated Power Density	Maximum Permissible Exposure	Fraction of MPE
	(MHz)		(watts)	(watts)	(feet)	(mW/cm ²)	(mW/cm ²)	(%)
Verizon	880	9	200	1800	160	0.0253	0.586	4.31%
Verizon	1900	3	200	600	160	0.0084	1	0.84%
Total Percentage of Maximum Permissible Exposure								5.16%

*Guidelines adopted by the FCC on August 1, 1996, 47 CFR Part 1 based on NCRP Report 86, 1986 and generally on ANSI/IEEE C95.1-1992

MHz = Megahertz

mW/cm² = milliwatts per square centimeter

ERP = Effective Radiated Power



ALP 9212-N


Log-Periodic Reflector Antenna

92 Degrees 12 dBd

Features:

- ☐ Broadbanded. (800-900 MHz)
- ☐ Low backlobe radiation. Front-to-back ratio better than 28 dB
- ☐ Low Intermodulation Products.
- ☐ Low Wind-load.
- ☐ Low weight.
- ☐ Small size.
- ☐ Rugged design.

Please see the following pages including radiation patterns/tables for ALP 9212-N.



Electrical Specifications:

Frequency range:	806-896 MHz
Impedance:	50 ohm
Connector:	N-female or 7/8" EIA
VSWR:	Typ. 1.3:1 max 1.5:1
Polarization:	Vertical
Gain:	12 dBd
Front to back ratio:	>28 dB
Side-lobe suppression:	>18 dB
Intermodulation: (2x25W):	IM3 >146 dB IM5 >153 dB IM7 & IM9 >163 dB
Power Rating:	500 W
H-Plane: -3 dB	95 °
E-Plane: -3 dB	15 °
Lightning Protection:	DC Grounded


Mechanical Specifications:

Overall Height:	52 in	(1320 mm)
Width:	11.4 in	(290 mm)
Depth:	11.4 in	(290 mm)
Weight including brackets:	26.7 lbs	(12 Kg)
Rated wind velocity:	113 mph	(180 Km/h)
Wind Area (Cx A/Front):	3.9 sq.ft	(0.36 sq.m)
Lateral thrust at rated wind		
Worst case:	570 N	

Materials:

Radiating elements:	Aluminum
Element housing:	Grey PVC
Back-plate:	Aluminum
Mounting hardware	
clamps:	Hot dip galvanized steel
bolts:	Stainless steel

Manufactured by: Allgon System AB



DECIBEL
Base Station Antennas

948F85T2E-M

16.1 dBi, Directed Dipole Antenna
1850-1990 MHz


1850-1990 MHz

MaxFill™


dB Director®

- Exceptional azimuth roll-off reducing soft hand-offs and improving capacity
- Excellent upper side lobe suppression
- Deep null filling below the horizon assures improved signal intensity
- Low profile appearance and low wind loading profile for easier zoning approvals


850



Azimuth 1850 MHz (Tilt=2)



Vertical 1850 MHz (Tilt=2)



Horizontal 1850 MHz (Tilt=2)



ELECTRICAL

Frequency (MHz):	1850-1990
Polarization:	Vertical
Gain (dBd/dBi):	14/16.1
Azimuth BW:	85°
Elevation BW:	8°
Beam Tilt:	2°
USLS* (dB):	>18
Null Fill* (dB):	15
Front-to-Back Ratio* (dB):	40
VSWR:	<1.33:1
IM Suppression - Two 20 Watt Carriers:	-150 dBc
Impedance:	50 Ohms
Max Input Power:	250 Watts
Lightning Protection:	DC Ground
Opt Electrical Tilt:	0°, 4°, 6°

MECHANICAL

Weight:	8.5 lbs (3.9 kg)
Dimensions (LxWxD):	48 X 3.5 X 7 in (1219 X 89 X 178 mm)
Max. Wind Area:	1.18 ft² (0.11 m²)
Max. Wind Load (@ 100mph):	65 lbf (289 N)
Max. Wind Speed:	125 mph (201 km/h)
Radiator Material:	Low Loss Circuit Board
Reflector Material:	Aluminum
Radome Material:	ABS, UV Resistant
Mounting Hardware Material:	Galvanized Steel
Connector Type:	7-16 DIN - Female (Bottom)
Color:	Light Gray
Standard Mounting Hardware:	DB390 Pipe Mount Kit, included
Downtilt Mounting Hardware:	DB5098, optional
Opt. Mounting Hardware:	DB5094-AZ Azimuth Wall Mount



Andrew Corporation
8635 Stemmons Freeway
Dallas, Texas U.S.A 75247-3701
Tel: 214.631.0310

Fax: 214.631.4706
Toll Free Tel: 1.800.676.5342
Fax: 1.800.229.4706
www.andrew.com

Date: 4/29/2004
* - Indicates Typical Values

dbtech@andrew.com

General Power Density

Site Name: Killingworth II, CT
Tower Height: 170 FT

Operator	Operating Frequency (MHz)	Number of Trans.	ERP Per Trans. (watts)	Total ERP (watts)	Distance to Target (feet)	Calculated Power Density (mW/cm ²)	Maximum Permissible Exposure* (mW/cm ²)	Fraction of MPE (%)
Verizon	880	9	200	1800	170	0.0224	0.586	3.82%
Verizon	1900	3	200	600	170	0.0075	1	0.75%
Total Percentage of Maximum Permissible Exposure								4.57%

*Guidelines adopted by the FCC on August 1, 1996, 47 CFR Part 1 based on NCRP Report 86, 1986 and generally on ANSI/IEEE C95.1-1992

MHz = Megahertz
mW/cm² = milliwatts per square centimeter
ERP = Effective Radiated Power





February 22, 2005

Steve Tuttle
Crown Castle International
500 West Cummings Park, Suite 3400
Woburn, MA 01801
(781) 729-4406

Vertical Structures, Inc.
309 Spangler Drive, Suite E
Richmond, KY 40475
(859) 624-8360
kmeehan@verticalstructures.com

Subject: Structural Analysis Report

Carrier Designation Verizon Wireless Change-Out
Carrier Site Number: N/A
Carrier Site Name: Killingworth 2

Crown Castle Designation Crown Castle BU Number: 807134
Crown Castle Site Name: NHV 031B
Crown Castle JDE Job Number: 59103

Engineering Firm Designation Vertical Structures Project Number: 2005-004-020

Site Data 197 North Chestnut Hill Road, Killingworth, CT, Middlesex County
Latitude 41°-23'-10.0", Longitude -72°-36'-16.0".
170' Rohn SSV Self-Supporting Tower

Dear Mr. Tuttle,


Vertical Structures is pleased to submit this structural analysis report to determine the structural integrity of the aforementioned tower. This analysis has been performed in accordance with the Crown Castle Structural 'Statement of Work' and the terms of Crown Castle Purchase Order Number 173037. The purpose of the analysis is to determine the suitability of the tower upon replacing three (3) existing panel antennas mounted on three (3) existing sector frames at 169' with six (6) proposed Decibel DB948F85T2E-M panel antennas for Verizon Wireless when combined with the existing and reserved equipment on the structure. This analysis has been performed in accordance with the TIA/EIA-222-F standard and local code requirements based upon a wind speed condition of 85 MPH.

Based on our analysis we have determined the tower superstructure and foundation are sufficient for the proposed loading.


Vertical Structures appreciates the opportunity of providing our continuing professional services to you and Crown Castle International. If you have any questions or need further assistance on this or any other projects please give us a call.

Respectfully submitted,

Kyle Meehan
Project Engineer



NHV 031B Report.doc



STATE OF CONNECTICUT

CONNECTICUT SITING COUNCIL

Ten Franklin Square, New Britain, CT 06051

Phone: (860) 827-2935 Fax: (860) 827-2950

E-Mail: siting.council@po.state.ct.us

www.ct.gov/csc

March 17, 2005

The Honorable Charles E. Bishop
First Selectman
Town of Guilford
31 Park Street
Guilford, CT 06437

RE: **EM-VER-026-060-070-070A-050317** – Cellco Partnership d/b/a Verizon Wireless notice of intent to modify an existing telecommunications facility located at 1919 Boston Post Road, Guilford; 49 Wig Hill Road, Chester; Route 80, Killingworth; and Chestnut Hill Road, Killingworth, Connecticut.

Dear Mr. Bishop:

The Connecticut Siting Council (Council) received this request to modify an existing telecommunications facility, pursuant to Regulations of Connecticut State Agencies Section 16-50j-72.

The Council will consider this item at the next meeting scheduled for April 19, 2005 at 1:30 p.m. in Hearing Room One, Ten Franklin Square, New Britain, Connecticut.

If you have any questions or comments regarding this proposal, please call me or inform the council by April 18, 2005.

Thank you for your cooperation and consideration.

Very truly yours,

S. Derek Phelps
Executive Director

SDP/cm

Enclosure: Notice of Intent

c: Regina Reid, Zoning Enforcement Officer, Town of Guilford



STATE OF CONNECTICUT

CONNECTICUT SITING COUNCIL

Ten Franklin Square, New Britain, CT 06051

Phone: (860) 827-2935 Fax: (860) 827-2950

E-Mail: siting.council@po.state.ct.us

www.ct.gov/csc

March 17, 2005

The Honorable David L. Denvir
First Selectman
Town of Killingworth
323 Route 81
Killingworth, CT 06419-1298

RE: **EM-VER-026-060-070-070A-050317** – Cellco Partnership d/b/a Verizon Wireless notice of intent to modify an existing telecommunications facility located at 1919 Boston Post Road, Guilford; 49 Wig Hill Road, Chester; Route 80, Killingworth; and Chestnut Hill Road, Killingworth, Connecticut.

Dear Mr. Denvir:


The Connecticut Siting Council (Council) received this request to modify an existing telecommunications facility, pursuant to Regulations of Connecticut State Agencies Section 16-50j-72.

The Council will consider this item at the next meeting scheduled for April 19, 2005 at 1:30 p.m. in Hearing Room One, Ten Franklin Square, New Britain, Connecticut.

If you have any questions or comments regarding this proposal, please call me or inform the council by April 18, 2005.

Thank you for your cooperation and consideration.

Very truly yours,



S. Derek Phelps
Executive Director

SDP/cm

Enclosure: Notice of Intent

c: Cathie Jefferson, Zoning Enforcement Officer, Town of Killingworth



STATE OF CONNECTICUT

CONNECTICUT SITING COUNCIL

Ten Franklin Square, New Britain, CT 06051

Phone: (860) 827-2935 Fax: (860) 827-2950

E-Mail: siting.council@po.state.ct.us

www.ct.gov/csc

March 17, 2005

The Honorable Martin L. Heft
First Selectman
Town of Chester
203 Middlesex Avenue
Chester, CT 06412-0218

RE: **EM-VER-026-060-070-070A-050317** – Cellco Partnership d/b/a Verizon Wireless notice of intent to modify an existing telecommunications facility located at 1919 Boston Post Road, Guilford; 49 Wig Hill Road, Chester; Route 80, Killingworth; and Chestnut Hill Road, Killingworth, Connecticut.

Dear Mr. Heft:

The Connecticut Siting Council (Council) received this request to modify an existing telecommunications facility, pursuant to Regulations of Connecticut State Agencies Section 16-50j-72.

The Council will consider this item at the next meeting scheduled for April 19, 2005 at 1:30 p.m. in Hearing Room One, Ten Franklin Square, New Britain, Connecticut.

If you have any questions or comments regarding this proposal, please call me or inform the council by April 18, 2005.

Thank you for your cooperation and consideration.

Very truly yours,

S. Derek Phelps
Executive Director

SDP/cm

Enclosure: Notice of Intent

c: Cathy Jefferson, Zoning Enforcement Officer, Town of Chester